



# FFC – Full-field Calibration

## Material characterization by consideration of the optically measured strain field

C. Ilg, D. Koch, M. Helbig, A. Haufe, K. Witowski (DYNAmore GmbH),  
N. Stander (LSTC), Åke Svedin (DYNAmore Nordic),  
M. Liewald, K. Drotleff (University of Stuttgart)

Nordic LS-DYNA Information Day 2017  
Göteborg, October 10, 2017



# Contents


- Motivation
- Preparations
- Implementation of FFC with LS-OPT
- Proof of concept
- Summary & conclusions
- Outlook

# Motivation

- Classical scheme of characterizing the yield behavior of a material
  - Tensile test – info: engineering stress-strain curve for a specific reference length
  - Adaption of the material parameters via a reverse engineering strategy, where the test is simulated and the resulting stress strain curves were compared to the testing results.
  - Drawbacks:
    - The area with the highest strains, the localization area, is not considered explicitly


# Motivation

- Traditional method for the evaluation of tensile tests
  - Engineering stress-strain curve with a predefined reference length (here:  $l_0 = 9 \text{ mm}$ )




# Motivation

- Traditional method for the evaluation of tensile tests
  - Engineering stress-strain curve for different reference lengths




# Motivation




# Preparations

- Evaluation of the optical measurement



# Preparations


- Evaluation of the optical measurement





# Preparations


- The simulation model



# Preparations


- The simulation model

Import in LS-PrePost




# Preparations

- The simulation model



# Preparations

- The simulation model



Boundary conditions:



No displacement (x,y,z)



No displacement (y,z) + displacement in x-direction


# Implementation of FFC with LS-OPT

- New interface in LS-OPT

1. Insert load stages

2. Definition of axes

3. Alignment of simulation and experiment




# Implementation of FFC with LS-OPT

- New interface in LS-OPT

Possibility to visualize the alignment in LS-PrePost

Selection of the variables from the simulation to be compared

Choose mapping method between test and simulation



# Proof of concept

- Material: sheet metal
- Assumptions and choices for the simulation model:
  - Simple and fast material model: \*MAT\_024  
(\*MAT\_PIECEWISE\_LINEAR\_PLASTICITY)
  - Reducing the number of free parameters for the yield curve description to two
  - Damage and failure are not considered

# Proof of concept

- Parametrization of the yield curve

Direct *calculation* of the yield curve until  $A_g$

$$\sigma_y = \sigma_{eng}(1 + \varepsilon_{eng})$$


$$\varepsilon_{pl} = \ln(1 + \varepsilon_{eng}) - \frac{\sigma_{eng}}{E}$$

*Extrapolation* from  $A_g$  with Hockett-Sherby

$$\sigma_y(\varepsilon_{pl}) = A - B e^{(-c \varepsilon_{pl}^n)}$$

$C^1$ -continuity at  $A_g$ :

- Reduction of the function by two variables





Remaining variables  $c$  and  $n$  are the optimization parameters





# Results

- Optimization with feedforward neuronal network (FFNN)



# Results

- Optimization with feedforward neuronal network (FFNN)



# Summary & conclusions

- Description of the disadvantages of classical yield curve adaption
- The FFC-method was compared with the classical method
  - Simple material model (\*MAT\_024)
  - Anisotropic effects and the influence of the yield locus were ignored
  - Damage and failure were not considered
- Implementation of a new FFC interface in LS-OPT
- The FFC-method is capable of providing at least equivalent results

# Outlook

- The multi-histories will be available in LS-OPT from the next release on
- Increasing the number of parameters to be optimized
  - More complex approach for yield curve extrapolation
  - Rolling direction
  - r-values (Lankford coefficients)
  - Yield locus
- Investigation of different, specimen geometries
- Future improvement of the LS-OPT interface
  - Visualizing the deviation between measurement and simulation

# Experimental material characterization at DYNAmore Stuttgart



**Contact:**  
DYNAmore GmbH  
Dr. André Haufe  
Industriestr. 2  
70565 Stuttgart  
fon: +49 (0)711 / 45 96 00 - 17  
email: andre.haufe@dynamore.de



M. Helbig



C. Ilg





D. Koch

## • Services

- Material deformation characterization and LS-DYNA material model calibration for:
  - Polymers
  - Foams
  - Metals
- Damage and fracture characterization and calibration for GISSMO and MAGD models

## • Experiments

- Tensile, bending, compression, punch test
- Component testing
- Local strain analysis with DIC





**Thank you!**